


COMPRESSOR DATA SHEET

Rotary Screw Variable Frequency Drive Compressor

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Ingersoll Rand	Date: August 16, 2010	
2	Model Number: R160Ne – W - 135 <input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled <input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free	# of Stages: 2	VALUE UNIT
3	Full Load Operating Pressure ^b	135	psig ^b
4	Maximum Full Flow Operating Pressure ^c	135	psig ^c
5	Drive Motor Nameplate Rating	200	hp
6	Drive Motor Nameplate Nominal Efficiency	96.1	percent
7	Fan Motor Nameplate Rating (if applicable)	0.8	kW
8	Fan Motor Nameplate Nominal Efficiency	86.6	percent
9	Input Power (kW)	Capacity (acfm) ^{a,c}	Specific Power (kW/100 acfm) ^e
	182.5	940.0	19.41
	161.8	840.3	19.26
	142.5	740.6	19.24
	124.1	641.0	19.36
	106.3	541.5	19.63
	88.5	441.4	20.05
	68.7	336.0	20.45
10	Total Package Input Power at Zero Flow ^d	0.0	kW ^d
11			

Note: Graph is only a visual representation of the data in section 9

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with the Annex E to ISO 1217. acfm is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. No Load Power. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in the Annex E to ISO 1217 as follows:

Volume Flow Rate at specified conditions		Volume Flow Rate ^f	Specific Energy Consumption ^g
<u>m³ / min</u>	<u>ft³ / min</u>	%	%
Below 0.5	Below 15	+/- 7	+/- 8
0.5 to 1.5	15 to 50	+/- 6	+/- 7
1.5 to 15	50 to 500	+/- 5	+/- 6
Above 15	Above 500	+/- 4	+/- 5

Member

