



NVC (4.2-227 m<sup>3</sup>/min / 150-8000 cfm)

Capacity Range: 150-8000 cfm (4.2-227 m<sup>3</sup>/min) Pressure Dew Point: 38°F (3°C) ISO Class 4 Cooling Method: Air-cooled and water-cooled Voltage: 230/1/60, 230/3/60, 460/3/60, 575/3/60, 230/1/50, 400/3/50 Maximum Pressure: 15-20 barg (220-300 psig) Maximum Ambient (air cooled): 120°F (49°C) Maximum Inlet Temperature: 120°F (49°C) Refrigerant: R-404A

## Features

- Cycling design results in ultimate energy savings
- Stainless steel heat exchangers
- Consistent dew point control ensures dry air at all times
- Easy to use, advanced microprocessor
- Environmentally friendly refrigerant



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit [www.ingersollrand.com](http://www.ingersollrand.com).